

AMENDMENTS

CLAIMS

Cancel claims 1, 3-16, 18-20 and 22 as set forth below.

1-20. (CANCELLED)

21. (PREVIOUSLY PRESENTED) An eaves trough support bracket, comprising:

- (a) a main beam having longitudinally spaced distal and proximal ends, laterally spaced first and second edges, and transversely spaced first and second surfaces;
- (b) a connection element extending in a first transverse direction from the distal end of the main beam;
- (c) a hook extending in the first transverse direction and a second longitudinal direction from the proximal end of the main beam, and defining a concavity open in a second transverse direction;
- (d) a first leg (i) extending in a second transverse direction from the first edge of the main beam with a proximal longitudinal end substantially transversely aligned with the proximal end of the main beam, and (ii) having a transverse height that tapers in the second transverse direction with a transverse height at the longitudinal center of the main beam of less than one half the transverse height at the proximal longitudinal end of the first leg; and
- (e) a second leg (i) extending in the second transverse direction from the second edge of the main beam with a proximal longitudinal end substantially transversely aligned with the proximal end of the main beam, and (ii) having a transverse height that tapers in the second transverse direction with a transverse height at the longitudinal center of the main beam of less than one half the transverse height at the proximal longitudinal end of the second leg.

22. (CANCELLED)